HYUNDAI SEASALL H10-SERIES 410ps [302kW] per ISO 3046



This modern, electronically controlled design delivers 410ps and 174kg·m of torque from the 10 liter in-line 6 cylinder engine.

The broad flat torque curve proves Hyundai SeasAll's diesel development capabilities are world-class and beats performance of competition's comparable models.

Economy is assured by the state-of-the-art fuel management system featuring Electronic Unit Injectors (EUI). The electronic engine control system makes the engine lighter, quieter and more fuel efficient with excellent compact dimensions.

The unique one-piece CGI (Compacted Graphite Iron) cylinder head makes the engine lighter and quieter than engines with conventional heads for more comfort onboard. Plus, longevity is assured with close to double the fatigue life of aluminum.

Technical Descriptions

Engine

- 6 cylinder in-line, 24 valve OHC
- One-piece Compacted Graphite Iron (CGI)
 cylinder head
- Cast iron cylinder block
- Gallery oil-cooled long lasting mono steel pistons
- Integrated water jacket
- Single serpentine belt system
- Drive belt auto-tensioner

Air Inlet system

- Reusable air filter
- Intake Extension Kit (Optional)

Fuel System

- Electronic Unit Injector (EUI)
- Gear-driven fuel pump
- Electronically controlled injection timing
- Fine fuel filter and water separator

Engine Mounting

Adjustable engine mounts (Optional)

Electrical System

- 24 volt 70A alternator
- Auxiliary engine stop button
- Air heating system for a trouble-free cold start
- NMEA2000 Converter (Optional)
- 2 Pole system (Optional)

Cooling System

- Gear-driven seawater pump
- · Seawater-cooled intercooler, heat exchanger
- · Auxiliary connector for cabin heating
- · Corrosion resistant material for seawater circuit
- Easily accessible seawater impeller pump

Lubrication System

- Easily exchangeable oil filter cartridge
- Integrated oil—cooler in cylinder block
- Closed system with forced feeding
- Eco type oil filter
- Electric oil extraction pump
- Gear drive engine oil pump
- Washable auxiliary cyclone oil filter

Instrument Box Assembly



- Engine self—protection and diagnosis
- Displays CAN information
- Displays engine diagnostic error codes
- Audible alarm and control lamps
- Idle & PTO rpm adjustable switch

Exhaust System

- Cast iron exhaust pipe
- E-VGT (Electric Variable Geometry Turbocharger)

Emissions

- IMO Tier II (EIAPP)
- US EPA Tier III
- CCNR Tier II

Type Approval

RINA Classification Society

Scope of Supply

	RATINGS ¹	ОМ	IBA ²	SeasLink***	BC**	DEP	SWP	TWO-POLE*	IEK**	NMEA 2000 C	SSS
H410	S1	٠	٠	0	٠	٠	٠	0	0	0	0
	OPERATION MAN		A=INSTRUM C=CONVER	ENT BOX ASSEMB TER SSS=SAFF	LY (WITH EC ETY STOP S	,	ELT COVER	DEP=DRY EXHAUST	ED PIPE	SWP=SEA WATER PUN	ЛР

1. RATINGS

S1 HEAVY DUTY COMMERCIAL

2. INSTRUMENT BOX ASSEMBLY includes EOI BOX, RPM GAUGE and WIRING HARNESS • : Standard \bigcirc : Option - : N/A S = Sterndrive P = Propeller Shaft J = Water Jet G = For Generator Pr = Prime Power Sb=Stand-by

🝠 HYUNDAI SEASALL


H410




Specifications


Engine Type	H410					
Propulsion system	Shaftdrive					
Engine Duty Rating	Heavy Duty (S1)					
Configuration	4-Stroke, 24-Valve OHC WGT with Intercooler, Fresh Water Cooling					
Output [ps (kW)]	410 (302)					
Rated rpm	2,000					
Cylinders	In-line 6					
Displacement [cc]	9,960					
Bore X Stroke [mm]	122 × 142					
Compression Ratio	16:1					
Max. Torque @ rpm	174.0kg·m @ 1,100 rpm					
Injection System	Electronic Unit Injector (EUI)					
Alternator	24V-70A					
Engine Diagnostics	YES					
Max Fuel Consump.[I/h]	81.8					
Dry Weight [kg]	1,120					
Flywheel	SAE 14					
Flywheel Housing	SAE 1					

Performance Curves



Dimensions (mm)







124 Jeongoksandan-ro, Seosin-myeon, Hwaseong-si, Gyeonggi-do 18554, Korea / Tel : +82-70-8620-8032 seasall.info@hyundai-seasall.com / Issued September 2019. Copyright © Hyundai SeasAll Co., Ltd. All Rights Reserved.